

DANDI-EYE

BRACING SYSTEM EYEBOLT

DANDI-EYE FORGED EYEBOLTS

Forged Eye-bolts designed to exceed the strength of the EHS bracing cable



- Meets ASCE 19-96 Standards for Structural Applications of Steel Cables for Buildings.
- Supplied with harden washers and nut. STRESS-LOK Clamping washer available for added strength.
- Shipped with material certifications when required.

SIZES | STRENGTHS

DANDI-EYE Sizes 6" Thread Length	Eye Opening	Min. Tensile Strength (lbs.)	Recommend Grip Size	Min. EHS Cable Strength (lbs)
1/2-13 x 8"	1-1/2"	8,500 lbs.	1/4"	6,650
5/8-11 x 8"	1-1/2"	13,600 lbs.	5/16"	11,200
3/4-10 x 8	1-1/2"	20,000 lbs.	3/8"	15,400
7/8-9 x 8"	1-1/2"	27,700 lbs.	1/2"	26,900

PROPERTIES

Material: Carbon steel (Grade 1)

Finish: .0003" zinc plated with clear chromate.

END FITTINGS

We provide BRACER® hillside washers for use with cable or rod bracing systems up to 1-1/2" diameter. BRACER® is independently tested to confirm the load capacities. Contact TFC for more information.

