

## TFC PRODUCT QUICK FACTS

- Drill and tap up to 1/2" thick steel.
- TRI-SEAL™ 1,000 hours salt spray coating.
- Available with patented back-out resistant VRT® Technology.
- Independent test results to confirm pullout capacities.

### Thread Types | Diameter

#8-18 (.164")  
 #10-16, #10-24 (.190")  
 #12-14, #12-24 (.216")  
 1/4-14, 1/4-20 (.250")  
 5/16-12 (.313")

### Lengths

1/2" up to 10"

### Point Types | Drilling

#### Thickness

DP1 (>.090")  
 DP3 (.036"-.250")  
 DP4 (.125"-.250")  
 DP5 (.250"-.500")

### Head Style

Pan Head, Mod Truss,  
 Hex Washer Head, Flat  
 Countersunk

### Drive Types

Cross Recess Square,  
 Hex Washer Head

### Materials

Carbon Steel, 304  
 Stainless,  
 410 Stainless

### Finish

Zinc plated, TRI-SEAL™  
 1,000 hrs salt spray  
 coating



www.trianglefastener.com

800.486.1832



## THE LARGEST SELECTION IN THE INDUSTRY

#8, #10, #12, 1/4", 5/16" | \*DP1, DP2, DP3  
 Carbon Steel | 410 Stainless Steel | TRI-SEAL®



#12, 1/4" | DP4, DP5  
 Carbon Steel | 410 Stainless Steel | TRI-SEAL®



*Sizes to meet all your  
 application needs!*

\*Available in VRT



U.S. Pat. No. 8,360,701  
 Taiwan Pat No. I50140  
 Europe Pat No. 2286067



#10, #12, 1/4" | Wood-to-Metal Carbon Steel | TRI-SEAL®



### PAINTED SCREWS AND ACCESSORIES



We can paint screws using  
 our KALIDA-KOTE custom  
 color match paint system.



We carry a full line of tools  
 and accessories for drilling,  
 driving, cutting and sawing.

DISCLAIMER: All information is non-binding and without guarantee. Before using the products, all specifications and calculations must be checked by a suitably qualified person and local regulations must be observed. This document is subject to revision. We reserve the right to make technical changes. (0321-1)

800.486.1832 | www.trianglefastener.com

MD262.0321

## TFC PRODUCT QUICK FACTS

- Drill and tap up to 1/2" thick steel.
- TRI-SEAL™ 1,000 hours salt spray coating.
- Available with patented back-out resistant VRT® Technology.
- Independent test results to confirm pullout capacities.

### Thread Types | Diameter

#8-18 (.164")  
 #10-16, #10-24 (.190")  
 #12-14, #12-24 (.216")  
 1/4-14, 1/4-20 (.250")  
 5/16-12 (.313")

### Lengths

3/4" up to 10"

### Point Types | Drilling

#### Thickness

DP1 (>.090")  
 DP3 (.036"-.250")  
 DP4 (.125"-.250")  
 DP5 (.250"-.500")

### Head Style

Hex Washer Head, Stainless Cap Head, Zinc Cap Head

### Drive Types

Hex Washer Head  
 T30 Torx Recess-Security

### Materials

Carbon Steel, 304 Stainless, 410 Stainless

### Finish

Carbon Steel, 410 SS:  
 TRI-SEAL™ 1,000 hrs salt spray coating.  
 304 SS: Zinc Plated

### Sealing Washers

EPDM Sealant  
 #8, #10: 12 mm O.D.  
 #12, 1/4": 15 mm O.D.



www.trianglefastener.com

800.486.1832



THE LARGEST SELECTION IN THE INDUSTRY

#10, #12, 1/4", 5/16" | \*DP1, DP2, DP3, DP4, DP5 | With Washer  
 Carbon Steel | 410 Stainless Steel | TRI-SEAL®



#12, 1/4" | \*DP1, DP3  
 Flange Seal | Carbon Steel | TRI-SEAL®



#12, 1/4", #17 | \*DP1, DP3 Type AB  
 Stainless Cap Head  
 Carbon Steel | TRI-SEAL®



### Security Screws

#12, 1/4" | \*DP1, DP3 | With Washer  
 Carbon Steel | TRI-SEAL®



\*Available in VRT



#12, 1/4" | \*DP1, DP3  
 Zinc Head | Carbon Steel | TRI-SEAL®



DISCLAIMER: All information is non-binding and without guarantee. Before using the products, all specifications and calculations must be checked by a suitably qualified person and local regulations must be observed. This document is subject to revision. We reserve the right to make technical changes. (0321-1)

800.486.1832 | www.trianglefastener.com

MD263.0321