

## The largest selection for the construction industry!

### Thin and Medium Gauge Applications | 29ga to 1/4"

#### BLAZER 1 - BLAZER 2 - BLAZER 3 Points



\*High Hex or Serrations Available

Blue colored sizes denotes popular DC items



5/16" HWH



U.S. Pat. No. 8,360,701  
Taiwan Pat No. I50140  
Europe Pat No. 2286067



\*5/16" HWH available in certain lengths.



Sliding Rake Angle Screw  
SSR Clip | 5/16" HWH



Want a screw that takes more force before bending?

Our NEW 5/16" diameter is 5-1/2 times stiffer than a 1/4-14 drill screw.

### Heavy Gauge Applications | 1/4" to 1/2"

#### BLAZER 4 & BLAZER 5 Points

- Drill and tap up to 1/2" thick steel.
- Supplied with our TRI-SEAL® long life coating for superior corrosion protection.
- Lengths up to 8" for retrofit metal roof base attachment.



#### HEX DRIVE SIZE

- #8 dia: 1/4" HWH
- #10 dia: 5/16" HWH
- #12 dia: 5/16" HWH
- 1/4 dia: 5/16" & 3/8" HWH
- 5/16 dia: 3/8" HWH



All screws are available with Bonded Sealing Washers. Call for sizes

- The hex washer head is the most popular drive system and provides the best stability during installation.
- Available with TRI-SEAL® long life coating for the ultimate corrosion protection...1,000 hrs salt spray with no red rust!

### SIZES AND PERFORMANCE SPECIFICATIONS

	Diameter   Length	Load Bearing Length (MAX)	Box Qty	Point Type	Drilling Thickness	
A	#8-18 x	1/2"	.100"	10M	BLAZER 2	.036" .100"
		5/8"	.125"	10M		
		3/4"	.250"	10M		
		1"	.500"	7.5M		
		1-1/4"	.750"	5M		
		1-1/2"	1"	5M		
B	#10-16 x	2"	1.5"	1.5M	BLAZER 3	.036" .175"
		1/2"	.100"	10M		
		5/8"	.125"	5M		
		3/4"	.250"	5M		
		3/4" HH/SERR	.250"	5M		
		1"	.500"	5M		
		1-1/2"	1"	3.5M		
		2"	1.500"	2M		
		3"	2.500"	1M		
		C	#12-14 x	3/4"		
1"	.250"			3.5M		
1-1/4"	.625"			3M		
1-1/2"	.750"			2M		
2"	1.25"			2M		
2-1/2"	1.75"			1M		
3"	2.25"			1M		
4" HWH	3.75			500		
D	1/4-14 x	7/8" VRT	.325"	2.5M	BLAZER 1/VRT	.036" .090"
		3/4"	.125"	2.5M	BLAZER 3	.036" .250"
		1"	.250"	2.5M		
		1-1/4"	.625"	2M		
		1-1/2"	.875"	2M		
		2"	1"	1.5M		
		2-1/2"	1.50"	1M		
		3"	2"	1M		
		4"	3"	500		
		5"	4"	500		
6"	2" - 5"	250				
8"	4" - 7"	250				
10"	6" - 9"	250				
E	1/4-14 x	1-1/4"	.625"	3.5M	BLAZER 3 SHLDR	.036" .210"
		1"	.250"	1.5M		
F	1/4-14 x	1-1/2"	.875"	1M	BLAZER 3	.036" .210"
		3"	2.25"	750		
		4"	3.25"	500		
		6"	2.50 - 5"	500		
		8"	4.25" - 7"	200		
G	5/16-12 x	7/8"	.325"	5M	BLAZER 4	.125" .250"
		1-1/4"	.500"	3M	BLAZER 4.5	.125" .375"
H	#12-24 x	1-1/4"	.500"	3M	BLAZER 5	.125" .500"
		1-1/2"	.625"	2M		
		2"	.750"	3M		
		1-1/2"	.500"	2M		
I	#12-24 x	2-1/4"	1.250"	1M	BLAZER 5	.200" .500"
		3-1/8"	2.125"	500		
		4"	3"	250		
		5"	4"	250		
		6"	2.50" - 5"	250		
		8"	4.25" - 7"	150		
J	1/4-20 x	4"	3"	250	BLAZER 5	.200" .500"
		5"	4"	250		
		6"	2.50" - 5"	250		
		8"	4.25" - 7"	150		

MATERIAL: C1018-1022 Carbon Steel

PLATING: .0003" Minimum Zinc Plated (48 hrs salt-spray)

Long-Life: TRI-SEAL® Coating (1,000hrs Salt Spray - ASTM B117).

Exceeds ASTM B633 and F1941 Standards

Dimensions: Meets or exceeds SAE J78 Standards