

Fluted Plastic Anchor



Base material - concrete, block, brick and stone

Anchor material - plastic

The Fluted Plastic Anchor is designed for light duty fastening applications with sheet metal or wood screws. Longitudinal ribs on the anchor body prevent it from turning during tightening of the screw. This inexpensive plastic screw anchor comes color-coded by diameter for easy application. The anchor is recommended for light duty static applications where holding power is not a critical factor. It should not be used overhead.

Cat. No.	Size	Color	Drill Dia.	Min. Depth	Std. Box	Std. Ctn.
7500	4-6 x 1	White	3/16	1	100	1000
7505	7-9 x 1	Red	7/32	1	100	1000
7510	10-12 x 1	Green	1/4	1	100	1000
7515	10-12 x 1 1/4	Green	1/4	1 1/4	100	1000
7520	10-12 x 1 1/2	Green	1/4	1 1/2	100	1000
7525	14 x 1	Blue	5/16	1	100	1000
7530	14 x 1 1/2	Blue	5/16	1 1/2	100	1000



Scru-Lead™

Base material - concrete and block

Anchor material - lead alloy

The Scru-Lead™ anchor is designed for use with sheet metal or wood screws in concrete, block or brick. The anchor is made entirely of lead alloy which is soft enough for easy installation, yet hard enough to give sure, secure holding power. The performance of this product depends on the integrity of the base material. The anchor is recommended for light duty applications where holding power is not a critical factor. It should not be used overhead.

Cat. No.	Size	Drill Dia.	Min. Depth	Std. Box	Std. Ctn.
9409	6-8 x 3/4"	1/4"	3/4"	100	1000
9414	6-8 x 1"	1/4"	1"	100	1000
9419	6-8 x 1 1/2"	1/4"	1 1/2"	100	1000
9429	10-14 x 1"	5/16"	1"	100	1000
9439	10-14 x 1 1/2"	5/16"	1 1/2"	100	1000
9460	16-18 x 1 1/2"	3/8"	1 1/2"	25	250

Lag Screw Sizes

Cat No.	Screw Size	Drill Dia.	Std. Box	Std. Ctn.
9080	3/8" x 2"	7/16"	25	250
9082	3/8" x 2 1/2"	7/16"	25	250
9084	3/8" x 3"	7/16"	25	250



Fiberplug™

Base material - concrete, block, brick, stone and plaster

Anchor material - jute fiber with lead liner


The Fiberplug™ is a jute fiber screw style anchor (formerly known as the Rawl (plug) designed for use in concrete, block, brick, stone, and plaster. Designed for use with wood, sheet metal and lag screws.

Cat. No.	Screw Size	Drill Dia.	Std. Box	Std. Ctn.	Mstr. Ctn.
9003	6 x 3/4"	5/32"	100	1000	5000
9005	6 x 1"	5/32"	100	1000	5000
9011*	8 x 3/4"	11/64"	100	1000	5000
9013	8 x 1"	11/64"	100	1000	5000
9015*	8 x 1 1/4"	11/64"	100	1000	5000
9017*	8 x 1 1/2"	11/64"	100	1000	5000
9024*	10 x 3/4"	3/16"	100	1000	5000
9026	10 x 1"	3/16"	100	1000	5000
9028	10 x 1 1/4"	3/16"	100	1000	5000
9030	10 x 1 1/2"	3/16"	100	1000	5000
9039	12 x 1"	1/4"	100	1000	5000
9041	12 x 1 1/4"	1/4"	100	1000	5000
9043	12 x 1 1/2"	1/4"	100	1000	5000
9045	12 x 2"	1/4"	100	1000	5000
9050	14 x 1"	9/32"	100	1000	5000
9052	14 x 1 1/4"	9/32"	100	1000	5000
9054	14 x 1 1/2"	9/32"	100	1000	5000
9056	14 x 2"	9/32"	100	1000	5000
9063	16 x 1 1/2"	5/16"	50	500	2500
9072	20 x 1 1/2"	3/8"	50	500	2500
9074	20 x 2"	3/8"	50	500	2500

* Discontinued item once current stock is exhausted



Fiberplug™ Fiber Screw Anchor



The Fiberplug™ is a jute fiber screw style anchor (formerly know as the Rawplug) designed for use in Concrete, block, brick, stone, and plaster. Designed for use with wood, sheet metal and lag screws.

Base Material: Concrete, Block, Brick


Size Range: 3/4" to 3/8" x 3"

Anchor Material: Jute Fiber With Lead Liner

Fiberplug™ Sheet Metal And Wood Screw Sizes

Screw Size	Drill Dia.	Std. Box	Std. Ctn.	Mstr. Ctn.
6" x 3/4"	5/32"	100	1000	5000
6" x 1"	5/32"	100	1000	5000
10" x 1"	3/16"	100	1000	5000
10" x 1-1/4"	3/16"	100	1000	5000
10" x 1-1/2"	3/16"	100	1000	5000
12" x 1"	1/4"	100	1000	5000
12" x 1-1/4"	1/4"	100	1000	5000
12" x 1-1/2"	1/4"	100	1000	5000
12" x 2"	1/4"	100	1000	5000
14" x 1"	9/32"	100	1000	5000
14" x 1-1/4"	9/32"	100	1000	5000
14" x 1-1/2"	9/32"	100	1000	5000
14" x 2"	9/32"	100	1000	5000
16" x 1-1/2"	5/16"	50	500	2500
20" x 1-1/2"	3/8"	50	500	2500
20" x 1"	3/8"	50	500	2500

Scru-Lead™ Lead Screw Anchor



The Scru-Lead™ anchor is designed for use with sheet metal or wood screws in concrete, block or brick. The anchor is made entirely of a lead alloy which is soft enough for easy installation, but hard enough to give sure, secure holding power.

The anchor is recommended for light duty applications where holding power is not a critical factor. It should not be used overhead.

Base Material: Concrete, Block, Brick

Size Range: No.6-8 x 3/4" to No.16-18 x 1-1/2"

Anchor Material: Lead Alloy

Fiberplug™ Lag Screw Sizes

Screw Size	Drill Dia.	Std. Box	Std. Ctn.
3/8" x 2"	7/16"	25	250
3/8" x 2-1/2"	7/16"	25	250
3/8" x 3"	7/16"	25	250

Scru-Lead™

Size	Drill Dia.	Min. Depth	Std. Box	Std. Ctn.
6-8" x 3/4"	1/4"	3/4"	100	1000
6-8" x 1"	1/4"	1"	100	1000
6-8" x 1-1/2"	1/4"	1-1/2"	100	1000
10-14" x 1"	5/16"	1"	100	1000
10-14" x 1-1/2"	5/16"	1-1/2"	100	1000
16-18" x 1-1/2"	3/8"	1-1/2"	25	250

Bantam Plug™



The Bantam Plug™ anchor is a plastic anchor designed for use with lightweight fixtures with a sheet metal or wood screws in concrete, block or brick. The anchor is recommended for light duty static applications where holding power is not a critical factor. It should not be used overhead.

Base Material: Concrete, Block, Brick, Wallboard

Size Range: No.6-8 x 3/4" to No.16-18 x 1-1/2"

Anchor Material: Plastic

Bantam Plug™

Size	Drill Dia.	Min. Depth	Std. Box	Std. Ctn.	Mstr. Ctn.
6-8" x 3/4"	3/16"	3/4"	100	1000	5000
8-10 x 7/8"	3/16"	7/8"	100	1000	5000
10-12 x 1"	1/4"	1"	100	1000	5000
14-16 x 1-1/2"	5/16"	1-1/2"	50	500	2500