



FASTENING SYSTEM

GYPFAST®

Fully Automatic Cordless Gas Fastening System for Attaching Exterior Sheathing to Light Gauge Steel Framing



Applications

- Exterior Gypsum sheathing to steel framing
- Plywood and OSB sheathing/flooring
- Fiber cement panel attachment
- Blocking
- Exterior walls
- Windows/door bucks
- Specialty exterior sheathing attachment
- Woven wire mesh or expanded metal lath to steel framing

Features

- Fully automatic system with 150 nail capacity is 3-5 times faster than screws.
- Fast set-up and tear down... insert battery, fuel cell and nail coil.
- Easy to use... self-contained power source eliminates need for extension cord, hoses and compressors.
- Aggressive, patented nail shank design provides high pullout performance.
- Contoured bugle head style provides high pullover (wind) resistance.
- Long life Climacoat™ finish is 10 times more corrosion resistant than electro-zinc plating.

Product Specifications

<i>Dimensions</i>	
Weight	8.9 lbs. (9.7 with nails)
Height	13.0 inches
Length	16.0 inches
<i>Nails</i>	
Lengths	1", 1-1/2", 2" and 2-1/2"
Diameter	.140" Nominal
Head Style	5/16" dia. bugle head
Finish	Climacoat Long Life Polymer
Fuel Cell	Liquid Hydrocarbon (1 cell/1,000 nails)

Approvals and Listings

- ICBO ER 5380 (Plywood diaphragm)
- ICBO ER 6070 (Gypsum sheathing)
- 3rd Party Independent Testing
 - Nail Withdrawl/Tensile Tests - Hardiplank® Report #3051160
 - Withdrawl Test - Report #3014672
 - Negative Wind Load Test - Report #J20044629-231-02
- Georgia Pacific Recognition Letter
- UL Fire Resistance Ratings
 - ANSI/UL 263
 - BX UV.V458



FASTENING SYSTEM

GYPFAST®



Corrosion Resistance:

Climacoat Long Life Polymer

- Salt Spray Results (ASTM B117)
Driven: 1560 hours, 10% or less red rust
UnDriven: 3240 hours, 10% or less red rust

Selection Chart

Part No.	Fastener Description .140" dia. Knurled Shank 5/16" dia. Bugle Head	Master Carton Quantity	Master Carton Weight	Applications
GF100	1" (25mm)	4,800 nails/ctn (48 - 100 ct. coils) 5 fuel cells	19 lbs.	Metal to Metal Attachment
GF112	1-1/2" (38mm)	6,000 nails/ctn (40- 150 ct. coils) 6 fuel cells	37 lbs.	Single Layer of Exterior Sheathing, Wood Furring and Blocking
GF200	2" (51mm)	4,800 nails/ctn (32 - 150 ct. coils) 5 fuel cells	38 lbs.	Double Layer of Exterior Gypsum Sheathing, Wood Furring and Blocking
GF212	2-1/2" (64mm)	2,700 nails/ctn (18 - 150 ct. coils) 3 fuel cells	26 lbs.	Multi-Layers of Sheathing, Wood Blocking, and Dimensional Lumber
GYPFAST	GypFast Cordless Coil Nailer 12 lbs. (1) Tool; (1) Safety Goggles; (1) Operators Manual			

Performance Data

ASTM E330 Negative Wind Load Results					
Fastener	Board Type	Orientation	Gauge	Stud Spacing	Stud/Fastener
GypFast	5/8" Dens-Glass® Gold	Vertical	18	24"/8"	70.9
GypFast	5/8" Exterior Gypsum	Vertical	18	24"/8"	63.5

Fastener Comparison/Performance						
Fastener	Pullout				Avg. lbs. Ultimate Tensile	Avg. lbs. Ultimate Shear
	Steel Gauge					
	20	18	16	14		
GypFast	.036	.048	.060	.075	2041	1385
S-12 self-drilling screws	194	327	437	930	750	1430

Values are in average, ultimate pounds.

Accessories

Part No.	Description	Carton (Qty)
2761910	Lath Disc Magnetic Nose Piece	1
LD114	Lath Disc - 1-1/4"	1000
LD100	Lath Disc - 1"	1000
405176	Battery	1
TFUEL	Fuel Cell	12
7505142	Battery Charger	1

Tools and Techniques

- Always read operators manual for instruction on proper use and safety.
- Adjust depth sensitive nosepiece to achieve proper seating of fastener to work surface.
- Consult sheathing manufacturer's guidelines for appropriate fastener and fastening pattern.
- Point of nail must penetrate 1/2" minimum beyond steel.



FASTENING SYSTEM

GYPFAST[®]AIR



Part No. GYPFASTAIR

GYPFAST[®]AIR



Part No. GYPFASTAIRHD

GYPFAST[®]HD

Pneumatic Systems for Attaching Exterior Sheathing to Light Gauge Steel Framing

Applications

- Exterior Gypsum sheathing to steel framing (20-14 gauge)
- Plywood and OSB sheathing/flooring
- Wood furring to steel framing
- Fiber cement panels to steel framing
- Woven wire mesh or expanded metal lath to steel framing

Features

- High performance pneumatic fastening system is 3-5 times faster than screws.
- 150 nails in a coil reduces reloading - improves productivity.
- Collation provides smooth, consistent operation with no flagging or breakage.
- Aggressive, patented nail shank design provides high pullout performance.
- Contoured bugle head style provides high pullover (wind) resistance.
- Long life Climacoat[™] finish is 10 times more corrosion resistant than electro-zinc plating.

Approvals and Listings

- ICBO ER 5380 (Plywood diaphragm)
- ICBO ER 6070 (Gypsum sheathing)
- Georgia Pacific Recognition Letter
- UL Fire Resistance Ratings
 - ANSI/UL 263
 - BX UV.V458
- 3rd Party Independent Testing
 - Nail Withdrawl/Tensile Tests - Hardiplank[®] Report #3051160
 - Withdrawl Test - Report #3014672
 - Negative Wind Load Test - Report #J20044629-231-02

Product Specifications

Dimensions	GypFast Air	GypFast Air HD
Weight	5.5 lbs.	6.0 lbs.
Height	13.0 inches	14.5 inches
Length	12.0 inches	13.5 inches
Nails		
Lengths	1", 1-1/2", 2" and 2-1/2"	
Diameter	.140" Nominal	
Head Style	5/16" dia. bugle head	
Finish	Climacoat Long Life Polymer	



ITW Ramset
700 High Grove Blvd., Glendale Heights, IL 60139
Phone: 630.825.7900 Fax: 630.893.1270
1.800.RAMSET6 (1.800.726.7386) www.ramset.com



FASTENING SYSTEM

GYPFAST[®]AIR



Corrosion Resistance:

Climacoat Long Life Polymer

- Salt Spray Results (ASTM B117)
 Driven: 1560 hours, 10% or less red rust
 UnDriven: 3240 hours, 10% or less red rust

Selection Chart



Part No.	Fastener Description .140" dia. Knurled Shank 5/16" dia. Bugle Head	Master Carton Quantity	Master Carton Weight	Applications
GF100A	1" (25mm)	4,800 nails/ctn (48 - 100 ct. coils)	18 lbs.	Metal to Metal Attachment
GF112A	1-1/2" (38mm)	6,000 nails/ctn (40 - 150 ct. coils)	36 lbs.	Single Layer of Gypsum, Sheathing, Wood Furring and Blocking
GF200A	2" (51mm)	4,800 nails/ctn (32 - 150 ct. coils)	37 lbs.	Double Layer of Gypsum Sheathing, Wood Furring and Blocking
GF212A	2-1/2" (64mm)	2,700 nails/ctn (18 - 150 ct. coils)	26 lbs.	Multi-Layers of Sheathing and Wood Blocking
GYPFAST AIR	GypFast Air Tool Kit (complete in a plastic carrying case) 10 lbs. (1) GypFast Air Tool; (1) Safety Goggles; (1) Operators Manual; (2) Hex Keys; (1) Oil			
GYPFAST AIR HD	GypFast Air HD Tool Kit (complete in a plastic carrying case) 10 lbs. (1) GypFast Air HD Tool; (1) Safety Goggles; (1) Operators Manual; (2) Hex Keys; (1) Oil			

Performance Data

Fastener	Board Type	Orientation	Gauge	Stud Spacing	Stud/ Fastener
GypFast	5/8" Dens Glass [®] Gold	Vertical	18	24"/8"	70.9
GypFast	5/8" Exterior Gypsum	Vertical	18	24"/8"	63.5

Per ITS Report No. J20044629-231-02.

Fastener	Pullout				Avg. lbs. Ultimate Tensile	Avg. lbs. Ultimate Shear
	Steel Gauge					
	20	18	16	14		
GypFast	.036	.048	.060	.075	2041	1385
S-12 self- drilling screws	194	327	437	930	750	1430

Values are in average, ultimate pounds.

Accessories

Part No.	Description	Carton (Qty)
2731910	Lath Disc Magnetic Nose Piece	1
LD114	Lath Disc - 1-1/4"	1000
LD100	Lath Disc - 1"	1000

Tools and Techniques

- Always read operators manual for instruction on proper use and safety.
- Adjust depth sensitive nosepiece to achieve proper seating of fastener to work surface.
- Consult sheathing manufacturer's guidelines for appropriate fastener and fastener spacing.
- Point of nail must penetrate 1/2" minimum beyond steel.