




Fiberplug™ Fiber Screw Anchor



The Fiberplug™ is a jute fiber screw style anchor (formerly know as the Rawplug) designed for use in Concrete, block, brick, stone, and plaster. Designed for use with wood, sheet metal and lag screws.

Base Material: Concrete, Block, Brick


Size Range: 3/4" to 3/8" x 3"

Anchor Material: Jute Fiber With Lead Liner

Fiberplug™ Sheet Metal And Wood Screw Sizes

Screw Size	Drill Dia.	Std. Box	Std. Ctn.	Mstr. Ctn.
6" x 3/4"	5/32"	100	1000	5000
6" x 1"	5/32"	100	1000	5000
10" x 1"	3/16"	100	1000	5000
10" x 1-1/4"	3/16"	100	1000	5000
10" x 1-1/2"	3/16"	100	1000	5000
12" x 1"	1/4"	100	1000	5000
12" x 1-1/4"	1/4"	100	1000	5000
12" x 1-1/2"	1/4"	100	1000	5000
12" x 2"	1/4"	100	1000	5000
14" x 1"	9/32"	100	1000	5000
14" x 1-1/4"	9/32"	100	1000	5000
14" x 1-1/2"	9/32"	100	1000	5000
14" x 2"	9/32"	100	1000	5000
16" x 1-1/2"	5/16"	50	500	2500
20" x 1-1/2"	3/8"	50	500	2500
20" x 1"	3/8"	50	500	2500

Scru-Lead™ Lead Screw Anchor



The Scru-Lead™ anchor is designed for use with sheet metal or wood screws in concrete, block or brick. The anchor is made entirely of a lead alloy which is soft enough for easy installation, but hard enough to give sure, secure holding power.

The anchor is recommended for light duty applications where holding power is not a critical factor. It should not be used overhead.

Base Material: Concrete, Block, Brick

Size Range: No.6-8 x 3/4" to No.16-18 x 1-1/2"

Anchor Material: Lead Alloy

Fiberplug™ Lag Screw Sizes

Screw Size	Drill Dia.	Std. Box	Std. Ctn.
3/8" x 2"	7/16"	25	250
3/8" x 2-1/2"	7/16"	25	250
3/8" x 3"	7/16"	25	250

Scru-Lead™

Size	Drill Dia.	Min. Depth	Std. Box	Std. Ctn.
6-8" x 3/4"	1/4"	3/4"	100	1000
6-8" x 1"	1/4"	1"	100	1000
6-8" x 1-1/2"	1/4"	1-1/2"	100	1000
10-14" x 1"	5/16"	1"	100	1000
10-14" x 1-1/2"	5/16"	1-1/2"	100	1000
16-18" x 1-1/2"	3/8"	1-1/2"	25	250

Bantam Plug™



The Bantam Plug™ anchor is a plastic anchor designed for use with lightweight fixtures with a sheet metal or wood screws in concrete, block or brick. The anchor is recommended for light duty static applications where holding power is not a critical factor. It should not be used overhead.

Base Material: Concrete, Block, Brick, Wallboard

Size Range: No.6-8 x 3/4" to No.16-18 x 1-1/2"

Anchor Material: Plastic

Bantam Plug™

Size	Drill Dia.	Min. Depth	Std. Box	Std. Ctn.	Mstr. Ctn.
6-8" x 3/4"	3/16"	3/4"	100	1000	5000
8-10 x 7/8"	3/16"	7/8"	100	1000	5000
10-12 x 1"	1/4"	1"	100	1000	5000
14-16 x 1-1/2"	5/16"	1-1/2"	50	500	2500