




# RIGID INSULATION ATTACHMENT TEKS® SELF DRILLING FASTENERS

Visit our website for the most up-to-date product and technical information!

## Interior Insulation Fasteners



The only self-driller designed for this unique application.

### Application

- Interior rigid and/or blanket insulation to steel frame.

### Head Style

- Maxiseal Hex Washer Head with Polyethylene Washer

Kesternich Results (DIN 50018, 2.0L)  
• 30 Cycles - 10% or less red rust

Salt Spray Results (ASTM B117)  
• 720 hours - 10% or less red rust



### Selector Guide

Part Number	Description	Head Style	Drill Point	Insulation Capacity	Range	Applications
1033200	12-14 x 1-7/8"	HWH	#3	.036-.210	3/4" to 1"	• Interior Rigid Insulation to Steel Frame
1035200	12-14 x 2-3/8"	HWH	#3	.036-.210	1-1/8" to 1-1/2"	
1037200	12-14 x 3-1/4"	HWH	#3	.036-.210	1-5/8" to 2-3/8"	
1039200	12-14 x 4"	HWH	#3	.036-.210	2-1/8" to 3"	


## Product Features

- Large polyethylene washer prevents over driving and pullover.
- Point has precise cutting edges to improve drill performance with less effort.
- Non-walking point provides fast material engagement.
- Point to thread design maximizes pullout performance and minimizes back out.
- Fastens the broadest range of insulation.
- White polyethylene washer matches insulation facers.

## Exterior Rigid Insulation Applications



The original self-drilling fasteners designed specifically for rigid insulation.



### Selector Guide

Part Number	Description	Head Style	Drill Point	Insulation Capacity	Range	Applications
<b>Maxiseal®</b>						
1034000	12-14 x 1-7/8"	HWH	#3	.036 - .210	3/4" to 1"	• Roof and wall panel over rigid insulation to steel framing.
1036000	12-14 x 2-3/8"	HWH	#3	.036 - .210	1-1/8" to 1-1/2"	
1038000	12-14 x 3-1/4"	HWH	#3	.036 - .210	1-5/8" to 2-3/8"	
1040000	12-14 x 4"	HWH	#3	.036 - .210	2-1/8" to 3"	
<b>Scots®</b>						
1169200	12-14 x 1-7/8"	HWH	#3	.036 - .210	3/4" to 1"	• Roof panel over spacer block and insulation to eave purlin.
1170200	12-14 x 2-3/8"	HWH	#3	.036 - .210	1-1/8" to 1-1/2"	
1171200	12-14 x 3-1/4"	HWH	#3	.036 - .210	1-5/8" to 2-3/8"	
1172200	12-14 x 4"	HWH	#3	.036 - .210	2-1/8" to 3"	

## Product Features

- Unique rider section stops panel jacking, point burnout and breakage.
- High thread under the head prevents panel strip out.
- Improved in place aesthetics.
- Available in Scots® and Maxiseal® head styles.
- Maximum pullover performance.
- Excellent driving stability.
- Seals when driven at an angle.
- Fastens the broadest range of insulation thickness.
- Point has precise cutting edges to improve drill performance with less effort.
- Non-walking point provides fast material engagement.
- Point to thread design maximizes pullout performance and minimizes back out.
- Climaseal® finish provides excellent corrosion resistance and lower tapping torque.

## Head Styles

Maxiseal Head



Scots Head

