

adhesives



OlyBond – The most trusted name in insulation attachment



OlyBond® Insulation Adhesives are easy to use, hassle-free and designed to get you off the roof and onto the next job fast. OlyBond adhesives are approved for use on most roof decks and with all common insulation types. Whether you have 10 squares or 10,000, there's an OlyBond adhesive that's right for your next project.

OlyBond500® is the premiere insulation adhesive for low-slope roofing applications. The fast-acting, dual-component, low-rise polyurethane foam adhesive is odor and noise-free, and offers the lowest installed cost method of insulation attachment. Factory Mutual, Underwriters Laboratories, Florida Building Code and Miami Dade approved.

OlyBond500 Green is the perfect insulation adhesive for LEED and sustainable projects. With environmentally sensitive packaging and a low VOC, plant-based formula, OlyBond500 Green packs the same performance punch as the original OlyBond500. Factory Mutual, Florida Building Code and Miami Dade approved.

OlyBond Classic is a spray-applied, dual component adhesive used to fully adhere a wide variety of board stocks to most roofing substrates in both new and reroofing applications.



Rest easy with **NightShot™** temporary watertight tie-in. OlyBond NightShot forms a temporary seal between new single-ply roof covers and existing asphalt roof covers. NightShot comes in 1,500 ml cartridge sets and is compatible with new EPDM, TPO and PVC materials.



application tools

OMG offers several easy-to-use tools for applying OlyBond500 Insulation Adhesives:

PaceCart 2® is the exclusive applicator for dispensing OlyBond500. Capable of dispensing enough OlyBond500 to apply 60 squares of insulation per hour, this tool is the fastest, lowest-cost system available. The patent-pending PaceCart 2 features a clean, air-tight delivery system for Bag-in-Box technology.

The **Cordless Power Applicator** provides constant pressure for even, uninterrupted, adhesive flow and maximum efficiency. The Power Applicator significantly increases production when compared to hand applicators, and comes with two batteries and a charger.





aluminum hercules




U-Flow Seal



Flow Control



Over Flow



Quick Flow

Drain Selector Guide

Product Name	Body Type / Thickness	Flange Diameter	Clamping Ring	Strainer Dome Type	Roof System Type	Notes
PC/PET RetroDrain	One piece PC/PET injection molded .150"	13.9"	PC/PET	PC/PET	Compatible with all types	Patented design built-in patented Olympic U-Flow Seal
Aluminum Hercules	One piece spun aluminum .125" (11 gauge)	17.5"	Cast Aluminum	Aluminum, PC/PET or SuperDome®	Compatible with all types	Includes patented Olympic U-Flow Seal
SuperDome RetroDrain	One piece PC/PET injection molded .150"	13.9"	PC/PET	SuperDome®	Compatible with all types	Patented design built-in patented Olympic U-Flow Seal
US-II RetroDrain	One Piece spun aluminum .064" (16 gauge)	17.5"	None	Aluminum or PC/PET	Compatible with all types except pitch	Includes patented Olympic U-Flow Seal
PVC AlumaWeld	One Piece spun aluminum .064" (16 gauge)	17.5"	None	Aluminum or PC/PET	Compatible with PVC	Plastisol flange or welding of PVC membranes. Includes Olympic U-Flow Seal
TPO RetroWeld	One piece TPO injection molded .150"	13.9"	PC/PET	SuperDome® or PC/PET	Compatible with TPO and EP Membranes	Hot air weldable flange for TPO and EP membranes. Includes Olympic U-Flow Seal
Copper Hercules	Tig welded copper .032" (3,4") .050" (5 &6")	17.5"	Cast Aluminum	Aluminum, PC/PET or SuperDome®	Compatible with all types	Includes patented Olympic U-Flow Seal
Aluminum Classic	One piece spun aluminum .125" (11 gauge)	12.5"	Cast Aluminum	Aluminum, PC/PET or SuperDome®	Compatible with all types	New construction applications. No compression seal