


**aluminum  
hercules**




**U-Flow Seal**



**Flow  
Control**



**Over  
Flow**



**Quick  
Flow**

### Drain Selector Guide

Product Name	Body Type / Thickness	Flange Diameter	Clamping Ring	Strainer Dome Type	Roof System Type	Notes
PC/PET RetroDrain	One piece PC/PET injection molded .150"	13.9"	PC/PET	PC/PET	Compatible with all types	Patented design built-in patented Olympic U-Flow Seal
Aluminum Hercules	One piece spun aluminum .125" (11 gauge)	17.5"	Cast Aluminum	Aluminum, PC/PET or SuperDome®	Compatible with all types	Includes patented Olympic U-Flow Seal
SuperDome RetroDrain	One piece PC/PET injection molded .150"	13.9"	PC/PET	SuperDome®	Compatible with all types	Patented design built-in patented Olympic U-Flow Seal
US-II RetroDrain	One Piece spun aluminum .064" (16 gauge)	17.5"	None	Aluminum or PC/PET	Compatible with all types except pitch	Includes patented Olympic U-Flow Seal
PVC AlumaWeld	One Piece spun aluminum .064" (16 gauge)	17.5"	None	Aluminum or PC/PET	Compatible with PVC	Plastisol flange or welding of PVC membranes. Includes Olympic U-Flow Seal
TPO RetroWeld	One piece TPO injection molded .150"	13.9"	PC/PET	SuperDome® or PC/PET	Compatible with TPO and EP Membranes	Hot air weldable flange for TPO and EP membranes. Includes Olympic U-Flow Seal
Copper Hercules	Tig welded copper .032" (3,4") .050" (5 &6")	17.5"	Cast Aluminum	Aluminum, PC/PET or SuperDome®	Compatible with all types	Includes patented Olympic U-Flow Seal
Aluminum Classic	One piece spun aluminum .125" (11 gauge)	12.5"	Cast Aluminum	Aluminum, PC/PET or SuperDome®	Compatible with all types	New construction applications. No compression seal