

Wood or Metal



TRACER® Flat Bugle Head

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
6 x 1"	3/8" - 5/8"	10
6 x 1 1/8"	3/8" - 3/4"	10
6 x 1 1/4"	3/8" - 7/8"	8
6 x 1 5/8"	3/8" - 1 1/4"	5
6 x 2"	1" - 1 5/8"	3.5
6 x 2 1/4"	5/8" - 1-7/8"	3
7 x 2 1/2"	7/8" - 2 1/8"	2.5
8 x 3"	1 3/8" - 2 5/8"	2
10 x 3 1/2"		1
10 x 4"		1
10 x 4 1/2"		1
10 x 5"		.5
10 x 6"		.5

Phos and oil



TRACER® Coarse Type "W"

Attachment of drywall to wood stud or framing.

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
6 x 1"	3/8" - 5/8"	10
6 x 1 1/8"	3/8" - 3/4"	10
6 x 1 1/4"	3/8" - 7/8"	8
6 x 1 5/8"	3/8" - 1 1/4"	5
6 x 2"	1" - 1 5/8"	3.5
6 x 2 1/4"	5/8" - 1 7/8"	3
7 x 2 1/2"	7/8" - 2 1/8"	2.5
8 x 3"	1 3/8" - 2 5/8"	2
10 x 3 3/4"		2
10 x 4"		1
10 x 4 1/2"		1
10 x 5"		.5
10 x 6"		.5

Phos and oil



Hi-Lo® Sharp Point

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
7 x 1"	3/8" - 5/8"	10
7 x 1 1/8"	3/8" - 3/4"	8
7 x 1 1/4"	3/8" - 7/8"	8
8 x 1 5/8"	1/2" - 1 1/4"	5
8 x 1 7/8"	3/4" - 1 1/2"	4
8 x 2 1/4"	1 1/16" - 1 7/8"	2.5
8 x 2 5/8"	1 3/8" - 2 1/4"	2.5
8 x 3"	1 7/8" - 2 5/8"	2



Need additional corrosion protection?

Now available with our TRI-SEAL™ coating for treated lumber applications!

Size: #6 x 1-1/4" GP Coarse thread. Phillips bugle head. 1,000 hrs salt spray



TRACER® Type "G"

Attachment or lamination of layered drywall.

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
10 x 1 1/2"	3/4" - 1"	5

Phos and oil



TRACER® Trim Head

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
6 x 1 5/8"	1/2" - 1 1/4"	5
6 x 2 1/4"	5/8" - 1 7/8"	3
6 x 3"	3/4" - 2 5/8"	2

Phos and oil



TRACER® Pan Head

Attachment of steel stud to steel track or for splicing steel stud up to 20 gauge (.036") total thickness.

Size/Length	Carton Quantity (M)
7 x 7/16"	10

Phos and oil



TRACER® D.S. Pan Framer

Attachment of steel stud of steel track or for splicing steel stud up to 14 gauge (.075") total thickness.

Size/Length	Carton Quantity (M)
6 x 7/16"	10
8 x 1/2"	10
8 x 1"	10

.00015" zinc plated zinc plated



TRACER® D.S. Round Washer Head

Attachment of wood trim thru drywall to steel stud up to 14 gauge (.075").

Size/Length	Carton Quantity (M)
8 x 1/2"	10
8 x 3/4"	5
8 x 1 1/4"	10

.00015" zinc plated zinc plated



BLAZER® Pan Head

Fastener for steel framing applications.

Size/Length	Head Type
8-16 x 5/8" DP2	Phillips pan

.00015" zinc plated zinc plated



BLAZER® Lo Profile Pancake Head

Fastener for steel framing applications.

Size/Length	Head Type
10-16 x 5/8" DP3	#2 square recess pancake

.0003" zinc and yellow



BLAZER® Lo Profile High Torq Pancake Head #2 Sq.

Fastener for steel framing applications.

Size/Length	Head Type
10-24 x 5/8" DP3 high torq	#2 Sq.Phil recess pancake

.0003" zinc and yellow



BLAZER® Hi-Hex

Fastener for steel framing applications. With serration.

Size/Length	Head Type
10-16 x 5/8" DP3	5/16" Hi-Hex design
10-16 x 3/4" DP3	

.0003" zinc plated



BLAZER® Heavy Gauge

Fastener for steel framing applications.

Size/Length	Head Type
12-24 x 1 1/4" DP5 heavy gauge up to 1/2"	5/16" HWH

.0003" zinc plated with long life coating.



BLAZER® Long-Pilot

Long pilot section allows the fastener to complete the drilling before tapping occurs, eliminating drill point failures.

Size/Length	Head Type
12-14 x 7/8" DP3	5/16" Hex washer head

Finish: .0003" min. electro zinc plated with flouropolymer topcoat.

Corrosion results: 1,000 hrs. salt spray

Applications: Drilling and tapping up to .210" thick steel.



STRESS-LESS® Framing Screw

Fastener for steel framing applications with high stress concentrations. Drill and tap up to 1/4" steel!

Size/Length	Head Type
1/4-14 x 7/8" DP3	5/16" Hex washer head
Epoxy Coated	

For technical data, refer to page 12.