



SA270

- Semi-automatic
- 2 1/2" pin capacity (3" w/ washer)
- 5-year warranty
- Uses Loadsaver™ 10-shot strip load

Specifications

.27 caliber	10-shot strip loads
	3 (Green)
	4 (Yellow)
	5 (Red)
Weight	5 3/4 pounds
Length	15 inches
Muzzle bushing O.D.	5/8"
Pin capacity	2 1/2" (3" w/washer)

Complies with OSHA and ANSI standards. ICBO Evaluation Service, Inc. – #ER-1147 (for sill plate applications)



VIPER

- Semi-automatic.
- 30% faster overhead attachment.
- 5-year warranty (10-year warranty on muzzle bushing).
- Uses Loadsaver™ 10-shot strip load.

Specifications

.27 caliber	10-shot strip loads
	3 (Green)
	4 (Yellow)
	5 (Red)
Weight	4.5 pounds
Pin capacity ceiling clips	1 1/4"
Length	17 inches

Complies with OSHA and ANSI standards.

L1600 LADD OVERHEAD FASTENING SYSTEM



.22 caliber crimped loads	4 (Yellow)
	5 (Red)
Weight	2.8 pounds
Height	13 inches

Complies with OSHA and ANSI standards.



- Single shot.
- .22 caliber crimped loads.
- It is important to use only loads specifically designed for use in the L1600 tool.
- Preassembled clip & pin speeds installation and reduces labor cost.
- Sturdiest clip on the market for improved pullover performance

- Accurate, positive attachment of hanger wire from concrete ceilings and steel.
- Elongated wire hole allows for freedom of movement of wire loop.
- 9/32" hole allows pencil rod to be suspended.
- No need for ladders or scaffolding with the LADD Fastening System.



- 1 Ejection pin
- 2 Barrel
- 3 Gas expansion chamber
- 4 Cartridge and chamber
- 5 Clip assembly