



Regular Round Head

Ring or Smooth Shank



Sizes and Quantities

#	Shank Length	Fastening Shank Gage Thickness	Required Range Max. Total Plywood	Required Deck Penetration Wood	Deck Penetration	Pieces/Pounds
1/16"		1		1/2"		12
		The		1/2"		109
1/16"		2		5/8"		12
		nail		5/8"		106
1/16"		3		3/4"		12
		must		3/4"		102
1/16"		4		7/8"		12
		pass		7/8"		99
1/16"		5		1"		12
		through		1"		96
1/16"		6	1	1/4"	12	1/4"

Design Options

Shank Types	Coating Types	Container Types	Cap Diameter	Nail Materials
1" Annular		Grooved		Bright 25 Lbs. Boxes
Smooth		Hi-Carbon		Steel
		Yellow Di-chromate		50 Lbs. Boxes
		Electro		Galvanized



Insulation Round Head

Ring or Smooth Shank

Sizes and Quantities

Nail Length	Shank Size	Head Diameter	Pieces Per Pound
1"	3"	9 ga.	
		44	
1"	3	1/2" 9 ga.	
		39	
1"	4"	9 ga.	
		36	
1"	5"	9 ga.	

Uses: BUR applications and other applications where thick insulation's are attached to wood substrates. Available in ring shank or smooth shank.



Masonry Round Head

Fluted Shank

1"	3/4"	9 ga.	
		84	
1"	1"	9 ga.	
		76	
1"	1	1/4" 9 ga.	
		64	



Plex-Cap® Plastic Cap Nails

Ring Shank

1"	3/4"	12 1/2 ga.	
		352	
1"	7/8"	12 1/2 ga.	
		318	
1"	1"	12 1/2 ga.	
		298	
1"	1 1/4"	12 1/2 ga.	
		274	
1"	1 1/2"	12 1/2 ga.	

Uses: For fastening applications of roofing felt, insulation, hose wraps, & polyfilm. Manufactured from high strength polymer plastic.



Square Cap Nail

1"	3/4"	12 ga.	
		63	
1"	7/8"	12 ga.	
		62	
1"	1"	12 ga.	
		61	