

Wood or Metal



TRACER® Fine - Type S

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
6 x 1"	3/8" - 5/8"	10
6 x 1 1/8"	3/8" - 3/4"	10
6 x 1 1/4"	3/8" - 7/8"	8
6 x 1 5/8"	3/8" - 1 1/4"	5
6 x 2"	1" - 1 5/8"	3.5
6 x 2 1/4"	5/8" - 1-7/8"	3
7 x 2 1/2"	7/8" - 2 1/8"	2.5
8 x 3"	1 3/8" - 2 1/8"	2
10 x 3 1/2"	1 7/8" - 3 1/8"	1
10 x 4"	2 3/8" - 3 5/8"	1

Phos and oil

SPECIFICATIONS

Head: Bugle Head with #2 Cross Recess
Finish: Phosphate (24hrs. salt spray)
TRACER® fasteners conforms to ANSI/ASME B18.6.4 and ASTM C1002-01
ASTM C1513-04



TRACER® Coarse - Type W

Attachment of drywall to wood stud or framing.

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
6 x 1"	3/8" - 5/8"	10
6 x 1 1/8"	3/8" - 3/4"	10
6 x 1 1/4"	3/8" - 7/8"	8
6 x 1 5/8"	3/8" - 1 1/4"	5
6 x 2"	1" - 1 5/8"	3.5
6 x 2 1/4"	5/8" - 1 7/8"	3
7 x 2 1/2"	7/8" - 2 1/8"	2.5
8 x 3"	1 3/8" - 2 5/8"	2
10 x 3 3/4"	2 1/8" - 3 3/8"	2
10 x 4"	2 3/8" - 3 5/8"	1

Phos and oil

SPECIFICATIONS

Head: Bugle Head with #2 Cross Recess
Finish: Phosphate (24hrs. salt spray)
TRACER® fasteners conforms to ANSI/ASME B18.6.1 and ASTM C1002-01

Need additional corrosion protection?

Now available with our TRI-SEAL® coating for treated lumber applications!

Size: #6 x 1-1/4" GP Coarse thread. Phillips bugle head.
1,000 hrs salt spray



TRACER HL | HIGH LOW

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
6 x 1"	3/8" - 5/8"	10
6 x 1 1/8"	3/8" - 3/4"	8
6 x 1 1/4"	3/8" - 7/8"	8
6 x 1 5/8"	1/2" - 1 1/4"	5
6 x 1 7/8"	3/4" - 1 1/2"	4
7 x 2 1/4"	1 1/16" - 1 7/8"	2.5
8 x 2 1/2"	15/16" - 2 1/8"	2.5
8 x 2 5/8"	1 3/8" - 2 1/4"	2.5
8 x 3"	1 7/8" - 2 5/8"	2



TRACER® Trim Head

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
6 x 1 5/8"	1/2" - 1 1/4"	5
6 x 2 1/4"	5/8" - 1 7/8"	3
6 x 3"	3/4" - 2 5/8"	2

Phos and oil

SPECIFICATIONS

Head: Bugle Head with #1 Square Recess
Finish: Phosphate (24hrs. salt spray)
TRACER® fasteners conforms to ANSI/ASME B18.6.4 and ASTM C1002-01



TRACER® Pan Head

Attachment of steel stud to steel track or for splicing steel stud up to 20 gauge (.036") total thickness.

Size/Length	Carton Quantity (M)
7 x 7/16"	10

Phos and oil



TRACER® Type "G"

Attachment or lamination of layered drywall.

Size/Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)
10 x 1 1/2"	3/4" - 1"	5

Phos and oil

SPECIFICATIONS

Head: Bugle Head with #2 Cross Recess
Finish: Phosphate (24hrs. salt spray)
TRACER® fasteners conforms to ANSI/ASME B18.6.1 and ASTM C1002-01