



Grommet Seal Fasteners are compression fasteners used in side-lap applications which utilize fiberglass, plastic or composite sheeting.


Sizes and Specifications

Grommet Size	1/4" x 1"	3/8" x 1"
Body Length	.948	.812
Nut Insert	6-32	10-32
Durometer (sleeve)	70	60
Ultimate Tensile	50 lbs.	80 lbs.

*Also available in 316 stainless steel.

Installation


The grommet is installed by placing it into a pre-drilled 1/4" or 3/8" hole and tightened using a screw gun with a standard 1/4" or 5/16" socket. The machine screw engages the nut insert, forcing the sleeve to expand against the inner wall of the materials. Grommets become an excellent sealant against air, moisture and vibration.



Machine Screw Size	6-32" x 1"	10-32" x 1"
Hex Size	1/4"	5/16"
Material	302 HQ	302 HQ
Bonded Washer	304 SS/EPDM	304 SS/EPDM
Sleeve	EPDM	EPDM
Nut Insert	Brass	Brass
Recommended		
Hole Size	.250	.375
Grip Range	.375-.607	.312-.450



More than forty years ago, the first Bulb-Tite® was developed to solve application requirements in the pre-engineered metal building, roofing and siding industry.



The Bulb-Tite® rivet body folds into three separate legs forming a large blind-side head. This large bearing head evenly distributes the Bulb-Tite® high clamp force in soft, thin or brittle materials while providing high pull through resistance. The Bulb-Tite® wide grip range enables a single Bulb-Tite® to work in a greater variation of thickness. Some versions of the Bulb-Tite® feature a special flush break mandrel that effectively seals the rivet bore and adds greater shear strength.

The standard Bulb-Tite® rivets are made of aluminum alloy, providing a durable non-rusting fastener that can withstand weather-related corrosion.

Bulb-Tite® Rivets handle your attaching problems with ease providing greater pull-through.




Sizes

With Sealing washer

	DIAMETER	TFC Part Number	GRIP	HOLE SIZE	SHEAR	TENSILE
A	3/16"	RV6604-6-4W	.062" - .250"	.209" - .221" (#4)	675	450
B	1/4"	RV6604-8-6W	.062" - .250"	.250" - .263" (1/4")	1,100	675
C	9/32"	RV6603-9-6W	.032" - .375"	.308" - .327" (5/16")	1,500	1,100
D	9/32"	RV6605-9-6W	.042" - .375"	.308" - .327" (5/16")	1,500	1,100

TOOLS

Tools designed to install Bulb-Tite® Rivets in metal clad building application.



Contact TFC for availability!